

BLOCK-LOCK ADHESIVE

PROVIDES A STRONG BOND WHEN USED TO ADHERE LANDSCAPE BLOCK WALL CAPS, THIN-BRICK PANEL SYSTEMS, ROOF TILES, ETC.

BLOCK-LOCK ADHESIVE is a premium adhesive which may be used for a variety of bonding applications such as adhering caps to landscape block walls, thin-brick panel systems and the installation of roof tile, valley tile, wall tile or broken field tile. Block-Lock Adhesive provides exceptional adhesion and resistance to tear, shear, stress and weathering. May be applied in a wide range of temperatures.

USES and ADVANTAGES

- Provides a strong durable bond when adhering caps to landscape block walls.
- Thin-brick veneer panel systems.
- Installation of roof tile, valley tile, wall tile or broken field tile.
- Adheres to concrete, brick, wood, tile, steel, asphalt, clay, slate, composite roof tiles and other common building substrates.
- One-part urethane, moisture cured.
- Contains no TDI (toluene diisocyanate).
- Fast-setting, no shrinkage.
- Easily applied with a standard caulk gun.
- Available in Gray.

SURFACE PREPARATION

Surfaces to which adhesive is being applied must be clean, dry, structurally sound and free of frost. All foreign materials such as dirt, dust, oils, grease, soot, loose paint, etc. should be removed before applying adhesive.

APPLICATION

Apply with conventional caulking equipment. For best results, apply adhesive in a zig-zag pattern. Warm

tube if temperature is below 40 °F (4 °C) for easier gunning.

Landscape Block

When installing caps onto landscape block walls, use a 1/4" bead (zig-zag pattern) approximately 2" in from the front and 2" in from the back. Then set cap by gently pushing down with a twisting motion. Keep foot traffic off landscape block wall caps for 24-48 hours after application.

Thin-Brick Panel Systems

Follow thin-brick panel manufacturer's specific instructions regarding proper preparation and installation.

Elongation.....994%

Tack Free.....45 minutes

Cure.....5 days

Service & Application Temperature:
-20 °F to 150 °F (-29 °C to 66 °C)

COVERAGE

One 10.6 oz. cartridge will yield approximately 24.1 linear feet at a 1/4" bead.

CLEANING

Uncured Block-Lock Adhesive may be easily removed from hands and tools with towels. Excess adhesive should be dry wiped from all surfaces and tools while uncured. Cured adhesive may be removed with a sharp blade.

NOTE: Cured adhesive is very difficult to remove without altering or damaging the surface to which it was applied.

PRECAUTIONS

- Do not use on plastic materials with high plasticizer content.
- Do not use on corrosive/crack sensitive plastics.
- Do not use for glazing.

APPLICATION STANDARDS

Meets ASTM C 920 Type S, Grade NS, Class 25, Use NT, A and M; Meets Federal Specification TT-S-0230C, Type II, Class A; Meets Canadian Specification CAN/CGSB-19.13-M87 Class 2 Non-sag, Class 25 M.

WARNING!

May cause respiratory or skin irritation. Do not breathe vapors. Use with adequate ventilation and wear protective clothing. Call a physician at the first sign of labored breathing. In case of contact, wash eyes/skin with water immediately. In case of fire, use water spray (fog), foam or CO2. Read Material Safety Data Sheet (MSDS) before using this product which may be obtained from your retailer or by calling 978-453-8881.

24 Hour Emergency Medical/Spill Information (Chemtrec): 800-424-9300.

KEEP OUT OF REACH OF CHILDREN.

For technical assistance call 978-453-8881

www.umaco.com

LIMITED WARRANTY

The manufacturer guarantees its products to be free of defects and the extent of its liability is limited to the purchase price of the materials only, if proved to be defective. Improper mixing, incorrect application or other factors beyond the control of the manufacturer or its dealers may produce unsatisfactory results and cannot be held to be the manufacturers or its dealers responsibility. There are no other guarantees either expressed or implied.

02-01-11



60 REAR NEWHALL STREET

PHONE: 978-453-8881

LOWELL, MA. 01852

FAX: 978-453-2416