

PAVER-LOCK SAND



PAVER-LOCK SAND is a unique blend of high grade silica sand and polymer binders designed to be swept into paver joints to keep pavers securely in place.



TAN



GRAY

- Ideal for patios, walks, sidewalks, driveways and pool sides
- Easy to install
- Keeps pavers securely in place
- May be used for sloping areas
- Reduces vegetation and weed growth
- Reduces ant hill formation
- Conforms to the specifications of the Interlocking Concrete Pavement Institute
- Available in Tan and Gray

Polymeric Sand	Apply by broom, sweeping into joints. Spray joints with water. Minimum Width = 1/8" Maximum Width = 1" Minimum Depth = 1.5"
Packaging	50 lb bag (49/pallet)
Coverage per 50 lb bag	Narrow joints = 75 ft ² Wider Joints = 35 ft ²
Application Temperature	Ambient & surface temperature must be 40°F or above and will not fall below that for 48 hours
Set Time @ 70°F, 50% RH	4 hours for foot traffic, 24 hours driveways



Phone: 800-442-5535
Fax: 978-453-2416
www.umaco.com

PAVER-LOCK SAND is a unique blend of high grade silica sand and polymer binders designed to be swept into paver joints to keep pavers securely in place. Paver-Lock Sand effectively reduces vegetation growth and ant infestation and will also reduce joint sand loss due to wind and precipitation erosion. Paver-Lock Sand conforms to the specifications of the Interlocking Concrete Pavement Institute (ICPI).

USES and ADVANTAGES

- Patios and sidewalks
- Driveways
- Pool sides
- Sloping areas
- Keeps pavers securely in place
- Reduces weed growth
- Reduces formation of ant hills
- Easy to install
- Available in Tan or Gray

MINIMUM JOINT WIDTH = 1/8"
MAXIMUM JOINT WIDTH = 1"
MINIMUM JOINT DEPTH = 1-1/2"

SURFACE PREPARATION

Follow paver manufacturer's specific instructions regarding proper preparation and installation.

Existing Pavers

Pressure wash all the paver joint filling material from the top of the paver to the bottom making sure that the joints are free of debris. Make sure that the top of pavers are completely dry before spreading Paver-Lock Sand.

New Pavers

Make sure that the top of pavers are completely dry before spreading Paver-Lock Sand.

APPLICATION

Spread the contents of the Paver-Lock Sand bags directly on the paving stones. Sweep the Paver-Lock Sand into the paver joints until all the joints are completely filled. Compact the sand and continue to sweep sand into the joints until all joints are completely filled and compacted. Remove all excess sand from the paver surface. Use of a leaf blower in addition to sweeping with a broom is recommended.

The removal of all excess sand is very important since it will be difficult to remove any residue left on the surface once pavers become wet.

CURING

Direct a fine spray of water in the air to dampen all Paver-Lock Sand joints. Allow the water to seep into the joints. Dampen until there is some water retention on the paver joints (about 30 seconds). Minimize or avoid walking on the pavers for at least 4 hours (after installation of Paver-Lock Sand. For driveways, let dry without traffic for at least 24 hours.

COVERAGE

Coverage will vary depending on the width of the joint and the size of the individual pavers but a good guideline is 75 ft² of coverage per 50 pound bag of Paver-Lock Sand for narrow joints and 35 ft² per 50 pound bag for wide joints.

PRECAUTIONS

- Only apply when the ambient and surface temperatures are 40°F or above and will remain so for a minimum of 48 hours
- Do not apply on wet or damp surfaces
- Avoid excessive watering or flooding of paver surfaces
- Do not apply if rain or any other precipitation is expected within 24 hours after application

WARNING!

Avoid breathing dust. This product contains silica which may cause cancer or delayed lung injury (silicosis). May be irritating to the eyes and skin. Avoid eye contact or prolonged contact with skin. In case of eye contact, flush with plenty of water for at least fifteen minutes. If irritation persists, seek immediate medical attention. Wash hands and skin thoroughly with water after handling. If irritation persists, seek immediate medical attention. Do not take internally. If ingested, seek immediate medical attention. NIOSH approved dust respirator, eye protection and gloves are recommended when using this product. Read Material Safety Data Sheet (MSDS) before using this product which may be obtained from your retailer or by calling 978-453-8881 or by visiting our website at www.umaco.com. 24 Hour Emergency Medical/Spill Information (Chemtrec): 800-424-9300
KEEP OUT OF THE REACH OF CHILDREN!

**For technical assistance call
978-453-8881**

www.umaco.com

LIMITED WARRANTY

The manufacturer guarantees its products to be free of defects and the extent of its liability is limited to the purchase price of the materials only, if proved to be defective. Improper mixing, incorrect application or other factors beyond the control of the manufacturer or its dealers may produce unsatisfactory results and cannot be held to be the manufacturers or its dealers responsibility. There are no other guarantees either expressed or implied.



2018

Umaco, Inc.
60 Rear Newhall Street
Lowell, MA 01852



Toll Free: 800-442-5535
Phone: 978-453-8881
Fax: 978-453-2416